

RECESSED EMERGENCY UNITS

Architecture Series



FD111A
Dimension: 15.75x5.75x4.76(inch)

Application

Ideal for commercial, industrial facilities where economy, appearance and the ultimate ease of installation and maintenance are desired. Also solid-state electronics to offer both reliability and low cost performance.

Standard Series Remote Capability



FD111B-RM
Dimension: 15.75x5.75x5.91(inch)

FD111C-RM
Dimension: 15.75x5.75x6.69(inch)

Features

Completely self-contained
Fully automatic operation
Compact, low profile design
Push to test switch
120/277V operation
FREEV 110v to 347V (option)
Automatic, Low voltage disconnected (LVD) protects battery from deep charge
SDT Self diagnostic (Option)
V-5/flame retardent, high impact.
UL924, ETL listed
Damp Location listed

6" IC SERIES



FD15A
Dimension: 13.31x10.91x9.06(inch)

FD15B

FD15G



4" IC

Dimension: 13.31x10.91x10.44(inch)

Dimension: 13.31x10.91x7.48(inch)

Dimension: 13.98x5.75x6.30(inch)

ORDERING INFORMATION

Series	Head Type	Bulb	Body Color	Option
FD111	A : MR 16 head	Blank : Incandescent 6v5.4w OR MR16 Halogen	Blank : White B : Black	SDT: Self Diagnostic
FD15	B : Round Head C : Square Head F : Auto clear E : LED Head			Test
		X : Xenon bulb 6v5.4w EL : 6V5W MR16 LED		FREEV: From 110v to 347V RM : Remote capability
				6V 35W: 635 6V 50W: 650 12V 35W: 1235 12V 50W: 1250