

EXIT SIGN

Standard Series



FD3R FD3G
Dimension:12.44x8.62x2(inch)

Application

Ideal for commercial,Industrial facilities where economy, appearance and the ultimate ease of installation and maintenance are desired,Also solid-state electronics to offer both reliability and low cost performance.

Features

Completely self-contained
Fully automatic operation
Compact,low profile design
Automatic,Low voltage disconnected (LVD) protects battery from deep charge
Push to test switch
120/277V operation
FREEV 110v to 347V (option)
Universal mounting
LED lamp life 25+ years
SDT Self diagnostic (Option)
V-5/flame retardant,high impact.
Energy Consumption of less than 2W and meets Energy Star.
(FD3N: Less than 1W, SMD LED)
UL924,ETL listed
Damp Location listed

Economy Series



FD3SCR FD3STG
Dimension:12.28x7.52x1.73(inch)

Delux & Compact SMD Series

(Power consumption : Less than 1 W)



FD3NR FD3NG
Dimension:11.34x7.44x1.85(inch)

100FT/All Directional Series

See the arrow in 100ft



FD43R FD43G
Dimension:21.26x10.20x2.56(inch)

ORDERING INFORMATION

Series	Light Panel	Emergency	Body Color	Option
FD3	R-Red	Blank : Battery back-up	Blank : White	SDT: Self Diagnostic
FD3SC	G- Green	AC: AC Power Only	B: Black	Test
FD3ST		ACDT : Dual Circuit/CAPACITOR		
FD3N		ACDTTR: DUAL CIRCUIT/TRANSFORMER		
FD43				