

HIGH CAPACITY(REMOTE CAPABILITY)EXIT SIGN

Standard Series



FD41MR(12w) 18 21 25 30
 Dimension:12.99X10.24X2.56(inch)

Compact Series



FD3MR FD3MG
 Dimension:12.64X8.62X2(inch)



FD3DMR
 Dimension:13.50X8.25X2.25(inch)



FD33W
 Dimension:13.19X9.45X2(inch)

Application

Ideal for commercial,Industrial facilities where economy, appearance and the ultimate ease of installation and maintenance are desired,Also solid-state electronics to offer both reliability and low cost performance.

Features

Completely self-contained
 Fully automatic operation
 Compact,low profile design
 Push to test switch
 120/277V operation
 FREEV 110v to 347V (option)
 Universal mounting
 LED lamp life 25+ years
 SDT Self diagnostic (Option)
 V-5/flame retardent,high impact.
 Energy Consumption of less than 3W and meets Energy Star.
 UL924,ETL listed
 Damp Location listed

Outdoor Type

ORDERING INFORMATION

Series	Light Panel	Emergency	Body Color	Option
FD41M	R-Red	Blank : Battery back-up	Blank : White	SDT: Self Diagnostic Test
FD3M	G- Green	AC: AC Power Only	B : Black	
FD3DM		ACDT : Dual Circuit/CAPACITOR		FREEV:From 110v to 347V
FD33W		ACDTTR: DUAL CIRCUIT/TRANSFORMER		
		12W:BLANK		
		18W:18		
		21W:21		
		25W:25		
		30W:30		