

COMBO(EXIT&EMERGENCY)SERIES

Economy Series



FD41G
Dimension:23.82x10.24x2.56(inch)

FD41R
Dimension:23.82x10.24x2.56(inch)

FD41FX-B
Dimension:23.32x10.24x2.56(inch)

Application

Ideal for commercial,Industrial facilities where economy, appearance and the ultimate ease of installation and maintenance are desired,Also solid-state electronics to offer both reliability and low cost performance.

Features

Completely self-contained
Fully automatic operation
Compact,low profile design
Push to test switch
Automatic,Low voltage disconnected (LVD) protects battery from deep charge
120/277V operation
FREEV 110v to 347V (option)
Universal mounting
LED lamp life 25+ years
SDT Self diagnostic (Option)
V-5/flame retardent,high impact.
Energy Consumption of less than 2W and meets Energy Star.
UL924,ETL listed
Damp Location listed

Classical Series



FD4OBR
Dimension:14.72x14.25x4(inch)

FD4OAR
Dimension:14.72x14.17x3(inch)

FD4OCR
Dimension:15.50x14.25x2.28(inch)

Compact & Slim Series



FD2BR
Dimension:20.24X8.62X2.76(inch)

FD2ER-B
Dimension:20X8.62X2.76(inch)

Slim Rotated Series



FD22FR
Dimension:21.65X8.62X3.15(inch)

FD22FXG

Side combo (New)

— Side Mounting —



FD41SFR
Dimension:17.72X10.24X4.57(inch)



FD41SBG
Dimension:17.72X10.24X4.57(inch)