

ARCHITECTURE EMERGENCY LIGHTING UNITS

Architecture Series



FD55E

Dimension:9.45x8.66x4.33 (inch)

FD55B

Dimension:9.45x8.27x3.94 (inch)

Application

Ideal for commercial,Industrial facilities where economy, appearance and the ultimate ease of installation and maintenance are desired,Also solid-state electronics to offer both reliability and low cost performance.

Features

Completely self-contained
Fully automatic operation
Compact,low profile design
Automatic,Low voltage disconnected (LVD) protects battery from deep charge
Push to test switch
120/277V operation
FREEV 110v to 347V (option)
SDT Self diagnostic (Option)
UL924,ETL listed
Damp Location listed

BRIGHT-GLOW (Indoor & Outdoor) Series

Heavy duty usage

The public place of more brighter and longer emergency lights required.
1600 LUMEN for 7HRS



FDD1
2X 13w

Dimension:9.72x7.09x4.92(inch)



FDD2
2X 13w

Dimension:10.63x7.28x5.43(inch)

ORDERING INFORMATION

Series	Bulb	Body Color	Option
FD55B	Blank : Incandescent 6v10w		SDT: Self Diagnostic Test
FD55E	or Mr16 6v10w	Blank : White	FREEV:From 110v to 347V
	X : Xenon bulb 6v5.4w	B : Black	ACDT : Dual circuit mode (FD55EEL)
	<u>EL : 6V5W MR16 LED</u>		DT : Dual Mode
D1	compact flourescent bulb		LAP : laster pointer testing...
D2	13W X 2		