

EMERGENCY LIGHTING UNIT

Architecture Series



FD5A FD5A-B
Dimension:14.72x5x3(inch)

Standard series



FD5B FD5B-B
Dimension:14.72x5x4(inch)

Auto Head Series (Clear & More Lumen)



FD5FX FD5FX-B
Dimension:15.35x5x3.82(inch)

Economy Series



FD5C FD5C-B
Dimension:15.5x5x3.82(inch)

Application

Ideal for commercial,Industrial facilities where economy, appearance and the ultimate ease of installation and maintenance are desired,Also solid-state electronics to offer both reliability and low cost performance.

Features

Completely self-contained
Fully automatic operation
Compact,low profile design
Automatic,Low voltage disconnected (LVD) protects battery from deep charge
Push to test switch
Laser pointer testing (LAP/option)
120/277V operation
FREEV 110v to 347V (option)
SDT Self diagnostic (Option)
Motion sensor(PPR) added
UL924,ETL listed
Damp Location listed

Beveled Series



FD5D FD5D-B
Dimension:14.72x5x3(inch)

Longlife Series 10hrs/Emergency Light



FD5EEL FD5EEL-B
Dimension:14.72x5x4(inch)

ORDERING INFORMATION

Series	Head Type	Bulb
FD5	A: MR16 6V5.4W	Blank : Incandescent 6v5.4w
	B: Round Head	OR MR16 Halogen
	C: Square Head	X : Xenon bulb 6v5.4w
	F : Auto head clear	EL : 6V5W MR16 LED
	E : Round MR16 Head	

Body Color	Option
Blank : White	SDT: Self Diagnostic Test
B : Black	FREEV:From 110v to 347V
	LAP : Lazer Pointer
	MT :Motion sensor added