

PHOTOLUMINESCENT EXIT SIGN

Standard Series

(Dimension)



FDPTR

FDPTG

Dimension:13.07(L)x8.31(w)(inch)

Economy Aluminium Extrusion Series



FDAEPTG

FDAEPTG

Dimension:13.66X8.86X0.67(inch)

Deluxe Die Casting Series



FDPHRB

FDPHGB

FDPHWW

FDPHBB

Dimension:13.39X8.27X0.87(inch)

Application

Non-electric PhotoLuminescent activate automatically when the lights dim or go out and function free of any human, mechanical or electrical intervention – even if all electric and battery sources fail. Photoluminescent needs no batteries or hard-wired electric power source. Photoluminescent materials are non-radioactive, free of toxic and hazardous substances, environmentally friendly and explosion-proof.

Feature

- * Pigment composed of Strontium Oxide Aluminates crystal.
- * Glows clearly in darkness and in a smoke-laden condition for at least 8 hours.
- * Re-charges fully in under an hour after light is restored.
- * The glow-in-the-dark property of the pigment will last indefinitely.
- * Products meet local building code requirements and certified UL 924 specifications as well as NFPA 101 Life Safety Code 2000 edition.
- * Products not only meet but also exceed the photoluminescent requirements of Local Law 26.
- * Products comply with The Americans With Disabilities Act(ADA) mandates for raised tactile characters, Braille, and non-glare finish.
- * Products can be installed in outdoor environment will generally last 10 to 20 years.

ORDERING INFORMATION

Series	Face Panel	HOUSING COLOR	Letter Size
FDPT	R:RED G:GREEN		Blank : 6" 8" : 8" Letter
FDAEPT	R:RED G:GREEN	BLANK : BRUSHED B:BLACK W:WHITE	
FDPH	R: RED G:GREEN W:WHITE B:BLACK AB:Al brushed	BLANK:Black W:White	